



Metro SHAKE Specification

ISS: 7/9/03 / REV: 4/9/2007

| | |
|------------------------------|---|
| Size | Length: 52.75" Cover Length: 50" Width: 16.5" Cover Width: 14.5" 20 pcs / Sq. |
| Accessories | STONE-COATED: Shake 'V' Cap for Ridge, Hip & Rake. / Fascia metal in 3-1/2" or 5" face widths X79". / Riser metal X 79". / Z-Bar X 79". / Valley Cover X 79". / Tie-In Metal X 79". / SMART-jack pipe flashing. / SMART-Sleeve pipe covers. / SMART-vent ventilator panels. PAINTED: Dbl 'V' Valley, Drip Edge, Side-Wall Underpan metal 120". |
| Protective Coating | *Galvalume® (*Reg. Trademark of BIEC Intl. Inc.) |
| Substrate | Steel — ASTM A-792 |
| Mechanical Properties | Grade 33 |
| Base Metal Thickness | .015" Inches |
| Coating Weight | AZ-50 *Galvalume® |
| Primer | *Galvalume® Plus or pigmented Color Coating |
| Minimum Pitch | 3:12 (12 Degrees) |
| Weight | 5.5 lbs. Each panel or 110 lbs. / Sq. |
| Pallet Size | 44" W X 55" L X 27" H = Contains 400 panels & Weighs 2,250 lbs. approximately, covering 20-squares |
| Exposed Fastened | BATTENS: Panels are installed from top of roof down to fascia. Standard install four (4) fasteners per panel through the front down turned nose. BATTEN-LESS: Direct to deck standard installs have four (4) fasteners through the back horizontal flange and four (4) through the front down turned nose of each panel, for a total per panel of eight (8) fasteners. |
| HVHZ | High Velocity Hurricane Zone areas require special fasteners and in a specific pattern. Refer to Metro's HVHZ install details for more information. |

Best Buy Metals

Toll Free 1-800-728-4010 / Phone 423-479-6382 / Fax 423-728-3066

www.BestBuyMetals.com