

FLORIDA DEPARTMENT OF  
**Business & Professional Regulation**



[BCIS Home](#) | [Log In](#) | [User Registration](#) | [Hot Topics](#) | [Submit Surcharge](#) | [Stats & Facts](#) | [Publications](#) | [FBC Staff](#) | [BCIS Site Map](#) | [Links](#) | [Search](#)



**Product Approval**  
 USER: Public User

License efficiently. Regulate fairly.

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**

OFFICE OF THE SECRETARY

FL #	FL7271-R2												
Application Type	Revision												
Code Version	2010												
Application Status	Approved												
Comments													
Archived	<input type="checkbox"/>												
Product Manufacturer	UNION CORRUGATING COMPANY												
Address/Phone/Email	701 S. KING ST. FAYETTEVILLE, NC 28301 (910) 483-0479 Ext 241 dpotts@unioncorrugating.com												
Authorized Signature	Dan Potts dpotts@unioncorrugating.com												
Technical Representative													
Address/Phone/Email													
Quality Assurance Representative													
Address/Phone/Email													
Category	Roofing												
Subcategory	Metal Roofing												
Compliance Method	Evaluation Report from a Florida Registered Architect or a Licensed Florida Professional Engineer <input checked="" type="checkbox"/> Evaluation Report - Hardcopy Received												
Florida Engineer or Architect Name who developed the Evaluation Report	Bala Sockalingam												
Florida License	PE-62240												
Quality Assurance Entity	Keystone Certifications, Inc.												
Quality Assurance Contract Expiration Date	12/31/2015												
Validated By	Yoosef Lavi, P.E. <input checked="" type="checkbox"/> Validation Checklist - Hardcopy Received												
Certificate of Independence	<a href="#">FL7271_R2_COI_CertificateIndependence.pdf</a>												
Referenced Standard and Year (of Standard)	<table border="0"> <thead> <tr> <th><b>Standard</b></th> <th><b>Year</b></th> </tr> </thead> <tbody> <tr> <td>ASTM E1592</td> <td>2001</td> </tr> <tr> <td>FM 4470</td> <td>1992</td> </tr> <tr> <td>TAS 125</td> <td>2003</td> </tr> <tr> <td>UL 1897</td> <td>1998</td> </tr> <tr> <td>UL 580</td> <td>1994</td> </tr> </tbody> </table>	<b>Standard</b>	<b>Year</b>	ASTM E1592	2001	FM 4470	1992	TAS 125	2003	UL 1897	1998	UL 580	1994
<b>Standard</b>	<b>Year</b>												
ASTM E1592	2001												
FM 4470	1992												
TAS 125	2003												
UL 1897	1998												
UL 580	1994												
Equivalence of Product Standards Certified By	Florida Licensed Professional Engineer or Architect <a href="#">FL7271_R2_Equiv_TestEquivalent_7271.pdf</a>												
Sections from the Code													
Product Approval Method	Method 1 Option D												
Date Submitted	11/25/2011												

Date Submitted 11/23/2011  
 Date Validated 12/08/2011  
 Date Pending FBC Approval 12/13/2011  
 Date Approved 01/31/2012

**Summary of Products**

FL #	Model, Number or Name	Description
7271.1	2-1/2" Corrugated Panel	Min 26 ga., 24" wide through fastened panel
<b>Limits of Use</b> Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-129.25 Other: Uplift load of 129.25 psf @ fastener spacing of 24" o.c. over 19/32" thick plywood		<b>Installation Instructions</b> <a href="#">FL7271_R2_II_D1805_9.pdf</a> Verified By: Bala Sockalingam PE 62240 Created by Independent Third Party: Yes  <b>Evaluation Reports</b> <a href="#">FL7271_R2_AE_EvaluationReportC1805_9.pdf</a> Created by Independent Third Party: Yes
7271.2	5V	Min 26 ga., 24" wide through fastened panel over 15/32" thick plywood
<b>Limits of Use</b> Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-66.3 Other: Uplift load of 66.3 psf @ fastener spacing of 12" o.c.		<b>Installation Instructions</b> <a href="#">FL7271_R2_II_D1805_10.pdf</a> Verified By: Bala Sockalingam PE 62240 Created by Independent Third Party: Yes  <b>Evaluation Reports</b> <a href="#">FL7271_R2_AE_EvaluationReportC1805_10.pdf</a> Created by Independent Third Party: Yes
7271.3	5V	Min 29 ga., 24" wide through fastened panel over 15/32" thick plywood or 7/16" thick OSB
<b>Limits of Use</b> Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-52.5 Other: Uplift load of 52.5 psf @ fastener spacing of 12" o.c.		<b>Installation Instructions</b> <a href="#">FL7271_R2_II_D1805_11_UL579.pdf</a> Verified By: Bala Sockalingam PE 62240 Created by Independent Third Party: Yes  <b>Evaluation Reports</b> <a href="#">FL7271_R2_AE_EvaluationReportC1805_11.pdf</a> Created by Independent Third Party: Yes
7271.4	5V	Min 26 ga., 24" wide through fastened panel over 19/32" thick plywood
<b>Limits of Use</b> Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: No Design Pressure: +N/A/-120.9 Other: Uplift load of 120.9 psf @ fastener spacing of 24" o.c. for Fastener Pattern 1. Uplift load of 85.8 psf @ fastener spacing of 24" o.c. and 113.1 psf @ fastener spacing of 12" o.c. for Fastener Pattern 2.		<b>Installation Instructions</b> <a href="#">FL7271_R2_II_D1805_12.pdf</a> Verified By: Bala Sockalingam PE 62240 Created by Independent Third Party: Yes  <b>Evaluation Reports</b> <a href="#">FL7271_R2_AE_EvaluationReportC1805_12.pdf</a> Created by Independent Third Party: Yes
7271.5	Advantage-Lok II	Min 26 ga., 16" wide concealed fastened panel over 15/32" & 19/32" thick plywood
<b>Limits of Use</b> Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: No Design Pressure: +N/A/-107.9 Other: Uplift load of 59.4 psf @ fastener spacing of 6" o.c. in 15/32" plywood. Uplift load of 97.5 psf @ fastener spacing of 6" o.c. with structural sealant in 15/32" plywood. Uplift load of 107.9 psf @ fastener spacing of 4" o.c. with structural sealant in 19/32" plywood.		<b>Installation Instructions</b> <a href="#">FL7271_R2_II_D1805_13.pdf</a> Verified By: Bala Sockalingam PE 62240 Created by Independent Third Party: Yes  <b>Evaluation Reports</b> <a href="#">FL7271_R2_AE_EvaluationReportC1805_13.pdf</a> Created by Independent Third Party: Yes
7271.6	MasterRib	Min 26 ga., 36" wide through fastened panel over 19/32" thick plywood
<b>Limits of Use</b> Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-114.3 Other: Uplift load of 61.8 psf @ fastener spacing of 30" o.c. and 114.3 psf @ fastener spacing of 24" o.c.		<b>Installation Instructions</b> <a href="#">FL7271_R2_II_D1805_14.pdf</a> Verified By: Bala Sockalingam 62240 Created by Independent Third Party: Yes  <b>Evaluation Reports</b> <a href="#">FL7271_R2_AE_EvaluationReportC1805_14.pdf</a> Created by Independent Third Party: Yes
7271.7	MasterRib	Min 29 ga., 36" wide through fastened panel over 15/32" thick plywood
<b>Limits of Use</b> Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-113.1		<b>Installation Instructions</b> <a href="#">FL7271_R2_II_D1805_15.pdf</a> Verified By: Bala Sockalingam PE 62240 Created by Independent Third Party: Yes  <b>Evaluation Reports</b>

<p><b>Other:</b> Uplift load of 45.0 psf @ fastener spacing of 24" o.c. &amp; 113.1 psf @ fastener spacing of 12" o.c.</p>		<p><b>Evaluation Reports</b>  <a href="#">FL7271_R2_AE_EvaluationReportC1805_15.pdf</a>                  Created by Independent Third Party: Yes</p>
7271.8	MasterRib	Min 29 ga., 36" wide through fastened panel over 15/32" thick plywood or 7/16" thick OSB
<p><b>Limits of Use</b>  <b>Approved for use in HVHZ:</b> No  <b>Approved for use outside HVHZ:</b> Yes  <b>Impact Resistant:</b> N/A  <b>Design Pressure:</b> +N/A/-52.5  <b>Other:</b> Uplift load of 52.5 psf @ fastener spacing of 12" o.c.</p>		<p><b>Installation Instructions</b>  <a href="#">FL7271_R2_II_D1805_16_UL584.pdf</a>                  Verified By: Bala Sockalingam PE 62240                  Created by Independent Third Party: Yes  <b>Evaluation Reports</b>  <a href="#">FL7271_R2_AE_EvaluationReportC1805_16.pdf</a>                  Created by Independent Third Party: Yes</p>
7271.9	MasterRib	Min 29 ga., 36" wide through fastened panel over nom. 1" x 4" furring and 15/32" thick plywood or 7/16" thick OSB
<p><b>Limits of Use</b>  <b>Approved for use in HVHZ:</b> No  <b>Approved for use outside HVHZ:</b> Yes  <b>Impact Resistant:</b> N/A  <b>Design Pressure:</b> +N/A/-114  <b>Other:</b> Uplift load of 71 psf for Fastener Pattern 1 &amp; 114 psf for Fastener Pattern 2</p>		<p><b>Installation Instructions</b>  <a href="#">FL7271_R2_II_D1805_17.pdf</a>                  Verified By: Bala Sockalingam PE 62240                  Created by Independent Third Party: Yes  <b>Evaluation Reports</b>  <a href="#">FL7271_R2_AE_EvaluationReportC1805_17.pdf</a>                  Created by Independent Third Party: Yes</p>
7271.10	ML200	Min 24 ga., max 16" wide standing seam metal panel with double lock seam over metal deck.
<p><b>Limits of Use</b>  <b>Approved for use in HVHZ:</b> No  <b>Approved for use outside HVHZ:</b> Yes  <b>Impact Resistant:</b> N/A  <b>Design Pressure:</b> +N/A/-116.0  <b>Other:</b> Uplift load of 71.0 psf @ clip spacing of 36" o.c. and 116.0 psf @ clip spacing of 12" o.c.</p>		<p><b>Installation Instructions</b>  <a href="#">FL7271_R2_II_D1805_18.pdf</a>                  Verified By: Bala Sockalingam PE 62240                  Created by Independent Third Party: Yes  <b>Evaluation Reports</b>  <a href="#">FL7271_R2_AE_EvaluationReportC1805_18.pdf</a>                  Created by Independent Third Party: Yes</p>
7271.11	PBR	Min 26 ga., 36" wide through fastened panel over 15/32" thick plywood
<p><b>Limits of Use</b>  <b>Approved for use in HVHZ:</b> No  <b>Approved for use outside HVHZ:</b> Yes  <b>Impact Resistant:</b> N/A  <b>Design Pressure:</b> +N/A/-52.5  <b>Other:</b> Uplift load of 52.5 psf @ fastener spacing of 12" o.c.</p>		<p><b>Installation Instructions</b>  <a href="#">FL7271_R2_II_D1805_19_UL638.pdf</a>                  Verified By: Bala Sockalingam PE 62240                  Created by Independent Third Party: Yes  <b>Evaluation Reports</b>  <a href="#">FL7271_R2_AE_EvaluationReportC1805_19.pdf</a>                  Created by Independent Third Party: Yes</p>
7271.12	SL175	Min 24 ga., max 16" wide snap-lock standing seam metal panel over metal deck.
<p><b>Limits of Use</b>  <b>Approved for use in HVHZ:</b> No  <b>Approved for use outside HVHZ:</b> Yes  <b>Impact Resistant:</b> N/A  <b>Design Pressure:</b> +N/A/-86.0  <b>Other:</b> Uplift load of 63.5 psf @ clip spacing of 36" o.c. and 86.0 psf @ clip spacing of 12" o.c.</p>		<p><b>Installation Instructions</b>  <a href="#">FL7271_R2_II_D1805_20.pdf</a>                  Verified By: Bala Sockalingam PE 62240                  Created by Independent Third Party: Yes  <b>Evaluation Reports</b>  <a href="#">FL7271_R2_AE_EvaluationReportC1805_20.pdf</a>                  Created by Independent Third Party: Yes</p>

[Back](#) [Next](#)

Contact Us :: [1940 North Monroe Street, Tallahassee FL 32399](#) Phone: 850-487-1824

The State of Florida is an AA/EEO employer. [Copyright 2007-2013 State of Florida.](#) :: [Privacy Statement](#) :: [Accessibility Statement](#) :: [Refund Statement](#)

Under Florida law, email addresses are public records. If you do not want your e-mail address released in response to a public-records request, do not send electronic mail to this entity. Instead, contact the office by phone or by traditional mail. If you have any questions, please contact 850.487.1395. \*Pursuant to Section 455.275(1), Florida Statutes, effective October 1, 2012, licensees licensed under Chapter 455, F.S. must provide the Department with an email address if they have one. The emails provided may be used for official communication with the licensee. However email addresses are public record. If you do not wish to supply a personal address, please provide the Department with an email address which can be made available to the public. To determine if you are a licensee under Chapter 455, F.S., please click [here](#).

Product Approval Accepts:

